

1. 4-door Sedan

A: DIMENSIONS

Model			2500
			AWD
Overall length	mm (in)		4,685 (184.4)
Overall width	mm (in)		1,745 (68.7)
Overall height (at CW)	mm (in)		1,415 (55.7)
Compartment	Leg room	Front Max.	mm (in) 1,101 (43.3)
		Rear Min.	mm (in) 868 (34.2)
	Head room	Front Max.	mm (in) 987 (38.9), 967 (38.1)*1
		Rear Min.	mm (in) 930 (36.6)
	Shoulder room	Front Max.	mm (in) 1,368 (53.9)
		Rear Min.	mm (in) 1,362 (53.6)
Wheelbase	mm (in)		2,650 (104.3)
Tread	Front	mm (in)	1,460 (57.5)
	Rear	mm (in)	1,460 (57.5)
Minimum road clearance	M.L.V.W.	mm (in)	115 (4.5)
	C.W.	mm (in)	155 (6.1)

*1: with sun roof

B: ENGINE

Model			2500
Engine type			Horizontally opposed, liquid cooled, 4-cylinder, 4-stroke gasoline engine
Valve arrangement			Overhead camshaft type
Bore x Stroke	mm (in)		99.5 x 79.0 (3.917 x 3.110)
Displacement	cm ³ (cu in)		2,457 (149.9)
Compression ratio			10.0
Firing order			1 — 3 — 2 — 4
Idle speed at Park/Neutral position	rpm		650 (MT), 700 (AT)
Maximum output	kW (HP)/rpm		123 (165)/5,600
Maximum torque	N.m (kg-m, ft-lb)/rpm		226 (23.0, 166)/3,600