

SPECIFICATIONS

Model	4W75 (Weedless gearcase) 4R75 (Standard gearcase)	Propeller gear ratio	17:28 (Weedless) 12:25 (Standard)	
*Horsepower (B.I.A. - certified)	4 hp at 4500 rpm	Propeller drive	Part Number 316558 1/8" x 1.234" stainless steel	
Full throttle op.-range	4000 to 5000 rpm	Propeller	Standard - 7-1/2" dia x 6" pitch, 3 blade LEXAN Weedless - 6-1/4" dia x 6" pitch, 2 blade LEXAN	
Test tank rpm with test wheel	4100 rpm Part Number 316021 for 4W75 4550 rpm Part Number 317738 for 4R75	Speed control	Single lever, synchronized throttle and spark	
Engine type	2 cylinder, 2 cycle alternate firing	Weight	Weedless - 34.0 lbs. Standard - 32.3 lbs.	
Bore and stroke	1-9/16" bore x 1-3/8" stroke	Hi Lift vacuum fuel system	3 gal. tank and plug in hose	
Piston displacement	5.28 cubic inches	Fuel capacity	3 gallons	
Piston ring sets (2 per set)		Starter	Swing-Arm, self-rewinding	
standard	Part Number 383920	Ignition	Flywheel magneto	
.030" oversize	Part Number 384312	Spark plug	AC-M44C, Champion J6J, - 14mm	
Diameter of ring	1.563 in. (standard)	Spark plug gap	.030 inch	
Width of ring	.0625 - .0615 in.	Spark plug torque	17-1/2 - 20-1/2 foot-pounds	
Lbs. compression recommended when compressed	1.3 to 2.8 lbs.	Breaker point gap	.020 inch	
Piston and ring assembly		Condenser	Part Number 580321	
standard	Part Number 384651	Capacity	.18 to .22 Mfd.	
.030" oversize	Part Number 384666	Coil	Part No. 580971	
Crankshaft size		COIL TEST SPECIFICATIONS		
top journal	.7520 - .7515 in.	Old Stevens Tester		
center journal	.6854 - .6849 in.	Switch	Index Reading	
bottom journal	.6854 - .6849 in.	A	2.0 - 2.5	
Connecting rod crank pin	.6255 - .6250 in.	New Stevens Tester Model No. M.A.-75		
Carburetion	Single barrel float feed, with high and low-speed adjustments manual choke	Switch	Index Adjustment	
Float level setting	Parallel with casting	B	22	
Inlet needle seat	.053 - .050 Use a #55 drill as gage.	Merc-O-Tronic		
Cooling system	Vari-volume (combination positive displacement and centrifugal pump).	Operating Amperage	Primary Resistance Min. Max. Secondary Continuity Min. Max.	
		1.6	.5 - .7 35 - 45	
		Graham Tester Model 51		
		Maximum Secondary	Maximum Primary	Coil Index
		5500	1.2	75
			Minimum Coil Test	Max. Gap Index
			33	75

*Horsepower established at sea level. Allow 2% reduction per 1000' above sea level.